

EVT400

Connected to one single panel.



-Type P



SAFE

Low DC voltage.



QUALITY

Components selected from world-class brands.



OPTIMIZATION

Individual MPPT for each module.



FLEXIBILITY

Adapts to any system size and optimizes space.



PLUG & PLAY

Hand-in-hand design, fewer add-ons, and fast installation.



15 YEARS

Long 25 years lifetime; optional up to 20 years warranty.



SMART*

Module-level online smart monitoring.

Smart*: Smart monitoring devices are optional at additional cost.



Monitoring Device EVB300

Communicates with Envertech microinverters and enables users to manage the systems in a smart digital way.

DATASHEET

Model	EVT400
Input Data (DC)	
Recommended Input Power Range(STC)	180W-550W+
Max. DC Input (V)	60V
Isc PV (Absolute Max.) (A)	25A
Operating Range (V)	16V-60V
Max. Input Current (A)	14A
MPPT Voltage Range (V)	22V-50V
Output Data (AC)	
Normal Voltage (Vac)	220V/230V
Voltage Range (Vac)	189-260V
Current (Max.continuous) (A)	1.81A
Frequency (Hz)	50Hz/60Hz
Frequency Range (Hz)	47.5-52.5Hz/57.5-62.5Hz
Power (Max.continuous) (W)	400W
Power Factor/Rated (default)	+/-0.90
Total Harmonic Distortion	<3%
Maximum Units Per Branch (12AWG Cable)	13 Units
Efficiency	
Peak Efficiency	96.5%
MPPT Efficiency	99.9%
Nighttime Power Consumption	< 100mW
Features	
Communication	PLCC(Power Line Carrier Communication)
Compliance	LVD 2014/35/EU, EMC 2014/30/EU, RED 2014/53/EU, ROHS, WEEE, REACH, EN 50549-1/10, IEC 62116&IEC 61727, VDE-AR-N 4105, VFR 2019, UTE C15-712-1, DIN VDE V 0126-1-1, C10/11, TOR, CEI 0-21, NC-RfG, NA/EEA-NE7 – CH 2020, NTS
Warranty	15 years (20 years optional)
Others	
Ingress Protection (IP)	IP 67
Protective Class	Class I
Temperature (C)	-40 °C to +65 °C
Relative Humidity	0% - 98%
Overvoltage Category	OVC III (AC Main), OVC II (PV)
Inverter Isolation	☑ High Frequency Isolated
Weight	1.8kg
Dimensions (W*H*D)	163.3mm*163.7mm*27mm