


EVT560

EVT720/800



Connected to two panels

-Type P



Smart*: Smart monitoring devices are optional at additional cost.



Monitoring Device EVBS

Communicates with Envertech microinverters and enables users to manage the systems in a smart digital way.

DATASHEET

Model	EVT560	EVT720	EVT800
Input Data (DC)			
Recommended Input Power Range(STC)	(180W - 450W+) *2	(180W - 500W+) *2	(180W-550W+)*2
Max. DC Input (V)	54V	60V	60V
Isc PV (Absolute Max.) (A)	15A	15A	25A
Operating Range (V)	18V-54V	16V-60V	16V-60V
Max. Input Current (A)	12A*2	12A*2	14A*2
MPPT Voltage Range (V)	24V-45V	22V-48V	22V-50V
Output Data (AC)			
Normal Voltage (Vac)	220V/230V	220V/230V	220V/230V
Voltage Range (Vac)	189-260V	189-260V	189-260V
Current (Max.continuous) (A)	2.72A	3.27A	3.63A
Frequency (Hz)	50Hz/60Hz	50Hz/60Hz	50Hz/60Hz
Frequency Range (Hz)	47.5-52.5Hz / 57.5-62.5Hz	47.5-52.5Hz / 57.5-62.5Hz	47.5-52.5Hz / 57.5-62.5Hz
Power (Max.continuous) (W)	600W	720W	800W
Power Factor/Rated (default)	+/-0.95	+/-0.90	+/-0.90
Total Harmonic Distortion	<3%	<3%	<3%
Maximum Units Per Branch (12AWG Cable)	8 Units	7 Units	6 Units
Efficiency			
Peak Efficiency	96.8%		
MPPT Efficiency	99.9%		
Nighttime Power Consumption	< 100mW		
Features			
Communication	PLCC (Power Line Carrier Communication)		
Compliance	VDE-AR-N 4105, IEC/EN61000,IEC/EN62109-1/2,EN50549-1/2019,TOR 2019,C10/11:2019,CEI 0-21 UTE C15-712-1:2013,VFR 2019 (See individual datasheet for specific product certifications)		
Warranty	15 years (20 years optional)		
Others			
Ingress Protection (IP)	IP 67		
Protective Class	Class I		
Temperature (°C)	-40°C to +65°C		
Relative Humidity	0% - 98%		
Overvoltage Category	OVC III (AC Main), OVC II (PV)		
Inverter Isolation	☑ High Frequency Isolated		
Weight	2.8kg	4.1kg	4.1kg
Dimensions (W*H*D)	248mm*169mm*27.5mm	264 mm*194 mm*35.5 mm	264 mm*194 mm*35.5 mm