CERTIFICATE OF CONFORMITY

Issued to:	Envertech (Shanghai) Corporation Ltd. Room 401, Block1, No.138, Xinjunhuan Road, Minhang District, 200014, Shanghai, P.R. China
For the product:	Micro inverter
Trade name:	ENVERTECH
Type/Model:	EVT2000, EVT2000SE, EVT1800SE, EVT1600SE, EVT1200, EVT1000, EVT900, EVT800, EVT800SE, EVT600, EVT560, EVT500, EVT450, EVT400, EVT360 and EVT350;
Ratings:	See Annex
Manufactured by:	Same as applicant
Factory:	Shanghai Chuangyineng Intelligent Technology Co., Ltd. 4 Floor, Zone C, Building 1, No.8 Shiyuan Road, Songjiang District, Shanghai, China
Requirements:	Engineering Recommendation G98 Issue 2: 2025 (G98/2)

Type of product certification scheme: Type 1a (Type approval)

This Test Certificate is granted on account of an examination by DEKRA, the results of which are laid down in a confidential file no. 6264836.50

The examination has been carried out on one single specimen of the product. The Attestation does not include an assessment of the manufacturer's production. Conformity of this production with the specimen tested by DEKRA is not the responsibility of DEKRA.

This Test Certificate expires at the latest on 27 August 2031 or expires upon withdrawal of one of the above mentioned standards.

Shanghai, 27 August 2026 Number: 6264836.01COC

DEKRA Testing and Certification (Shanghai) Ltd.

Kreny Lin
Certification Manager

IAS ACCREDITED Product Certification Agency

© Integral publication of this certificate and adjoining reports is allowed

PCA-141

Annex

Document no. : 6264836.01COC

Model ratings:

EVT350:
Input: 16~60V DC, MPPT voltage range 22-50V DC, Max. 14A
Output: 220/230V, 50/60Hz, 350W, Max.1.59A

EVT360:
Input: 16~60V DC, MPPT voltage range 22-50V DC, Max. 14A
Output: 220/230V, 50/60Hz, 360W, Max.1.64A

EVT400:
Input: 16~60V DC, MPPT voltage range 22-50V DC, Max. 14A
Output: 220/230V, 50/60Hz, 400W, Max.1.81A

EVT450:
Input: 16~60V DC, MPPT voltage range 22-50V DC, Max. 16A
Output: 220/230V, 50/60Hz, 450W, Max.2.05A

EVT500:
Input: 16~60V DC, MPPT voltage range 22-50V DC, Max. 18A
Output: 220/230V, 50/60Hz, 500W, Max.2.27A

EVT560:
Input: 16~60V DC, MPPT voltage range 22-50V DC, Max. 9.5A*2
Output: 220/230V, 50/60Hz, 560W, Max.2.54A

EVT600:
Input: 16~60V DC, MPPT voltage range 22-50V DC, Max. 14A*2
Output: 220/230V, 50/60Hz, 600W, Max.2.73A

EVT800:
Input: 16~60V DC, MPPT voltage range 22-50V DC, Max. 14A*2
Output: 220/230V, 50/60Hz, 800W, Max.3.63A

EVT900:
Input: 16~60V DC, MPPT voltage range 22-50V DC, Max. 16A*2
Output: 220/230V, 50/60Hz, 900W, Max.4.09A

EVT1000:
Input: 16~60V DC, MPPT voltage range 22-50V DC, Max. 18A*2
Output: 220/230V, 50/60Hz, 1000W, Max.4.55A

EVT1200:
Input: 16~60V DC, MPPT voltage range 22-50V DC, Max. 20A*2
Output: 220/230V, 50/60Hz, 1200W, Max.5.45A

EVT2000:
Input: 16~60V DC, MPPT voltage range 22-50V DC, Max. 18A*4
Output: 220/230V, 50/60Hz, 2000W, Max.9.09A

Annex

Document no. : 6264836.01COC

EVT800SE:
Input: 16~60V DC, MPPT voltage range 22-50V DC, Max. 14A*2
Output: 220/230V, 50/60Hz, 800W, Max.3.63A
EVT1600SE:
Input: 16~60V DC, MPPT voltage range 22-50V DC, Max. 20A*4
Output: 220/230V, 50/60Hz, 1600W, Max.7.27A
EVT1800SE:
Input: 16~60V DC, MPPT voltage range 22-50V DC, Max. 20A*4
Output: 220/230V, 50/60Hz, 1800W, Max.8.18A
EVT2000SE:
Input: 16~60V DC, MPPT voltage range 22-50V DC, Max. 20A*4
Output: 220/230V, 50/60Hz, 2000W, Max.9.09A

Model	EVT350, EVT 360, EVT400, EVT450 and EVT500		EVT560, EVT600, EVT800, EVT800SE, EVT900, EVT1000 and EVT1200		
Hardware version	EVT300_V6.1X	EVT400_V6.5X	EVT720_V6.1X	EVT720_V6.2X	EVT800_V6.5X
Software version	P127 S126	P127 S133	P127 S126	P127 S133	

Model	EVT1600SE, EVT1800SE and EVT2000SE	EVT2000
Hardware version	EVT2000SE_V0.82	EVT2000_V0.77
Software version	P164 S126	P164 S126

--- End ---